



## Smart Security IP Intercom - IS710v2




The ESCENE IP Intercom - IS710 (V2), has been developed to customers' needs. Its classic fascia design is waterproof, dustproof and vandal resistant. It is ideal for many applications where SIP connectivity is required.

### Product Features

- One button calling with full-duplex voice intercom.
- Fascia is 5mm thick drawn aluminum for strength and durability.
- Supports POE and local 12v power supply.
- Flush mount or surface mount with the surface mount cabinet supplied as standard.
- Two relays for releasing 2 doors or activating 2 devices.
- Gasket seals provide waterproof and dustproof level to IP65.
- Two input sensors for monitoring or egress button use.

## Technical Information

<b>Intercom features</b>
<ul style="list-style-type: none"><li>• WEB support Multi-Language</li><li>• 1 SIP account</li><li>• Hotline, Call forward, DND, Auto-answer, Volume control</li><li>• Default Ring tone selection/import/delete, Custom Warning Ring tone selection/import/delete</li><li>• Time setting (SNTP/SIP Server/Manual)</li><li>• Support SIP main/standby server</li></ul>
<b>Network parameters</b>
<ul style="list-style-type: none"><li>• SIP v1 (RFC2543), v2 (RFC3261), DNS SRV (RFC3263)</li><li>• NAT Traversal: STUN mode.</li><li>• DTMF: In-Band, RFC2833, SIP Info, Auto</li><li>• HTTP/HTTPS Web Management</li><li>• IP Assignment: Static/DHCP/PPPoE</li><li>• Network support Bridge mode; TFTP/DHCP/PPPoE</li></ul>
<b>Security</b>
<ul style="list-style-type: none"><li>• LLDP, VLAN QoS (802.1pq), VPN(L2TP)</li><li>• Transport Layer Security (TLS)</li><li>• Digest authentication using MD5/MD5-sess. secure configuration file via AES encryption;</li></ul> Phone lock for personal privacy protection; Admin/User 2-level configuration mode.
<b>Voice features</b>
<ul style="list-style-type: none"><li>• Wideband Codec: G.722</li><li>• Narrowband codec: G.711<math>\mu</math>/A, G.723.1;G.726, G.729a/b, iLBC; VAD, CNG, AEC,</li></ul>
<b>Physical properties</b>
<ul style="list-style-type: none"><li>• 1 hotline programmable key (Speed dial, Intercom etc.); 1 light touch button</li><li>• 1xRJ45 10/100M Ethernet ports; PoE, IEEE 802.3af, class 0.</li><li>• Power adapter: AC 100~240V input DC 12V/1A output;</li><li>• Net weight: 0.52KG, Gross weight: 0.65KG.</li></ul> Each motherboard port, check the picture illustration below "Mother Board Interface".
<b>Carton packaging</b>
The whole Size : 162*112*40mm
<b>Product Certification</b>

<b>Platform Compatibility Test (non-certificate)</b>
ZTE/Alcatel-Lucent/Asterisk/Broadsoft/Metaswitch/Yeastar/Avaya/3CX/Elastix/HUAWEI etc.



Your Escene agent:

Active Online  
Freecall: 1300 816 742  
www.activeonline.com.au