

## Accessories | Electronic Door Strikes

Model	ACLOC100	ACLOC101	ACLOC102	ACLOC103	ACLOC104
Image					
Type	Mortise Mount	Surface Mount	Mortise Mount	Mortise Mount	Surface Mount
Door Latch	9.5mm	9.5mm	12.7mm	12.7mm	9.5mm
Keeper Depth	9.6mm	9.6mm	12.7mm	10.8mm	9.6mm
Construction	Steel	Steel	Stainless Steel	Stainless Steel	Chrome Plated Steel
Lock Configuration	Fail Secure	Fail Secure	Fail Secure / Fail Safe	Fail Secure / Fail Safe	Fail Secure
Lock Status Sensor	No	No	Yes	Yes	No
Power Input	12VDC at 400mA	12VDC at 400mA	12VDC at 260mA	12/24VDC at 280/140mA 12/24VAC at 170/85mA	12VDC at 400mA
Faceplate Dimensions	160 x 25 x 3mm	108.5 x 50 x 3mm	165 x 31 x 2mm	175 x 29 x 3mm	175 x 29 x 3mm
Overall Dimensions	160 x 25 x 30.8mm	108.5 x 50 x 31.4mm	165 x 31 x 40.2mm	175 x 29 x 26mm	144.5 x 36.4 x 25mm

## Accessories | Electronic Magnetic Locks

Model	MAGLOC100S	MAGLOC100M	MAGLOC101S	MAGLOC101M
Image			<span style="background-color: green; color: white; border-radius: 50%; padding: 2px;">Coming Soon</span>	<span style="background-color: green; color: white; border-radius: 50%; padding: 2px;">Coming Soon</span>
Type	Surface Mount	Mortise Mount	Surface Mount	Mortise Mount
Holding Force	Approx. 270kg			
Construction	Anodised Aluminium with zinc finish			
Lock Configuration	Fail Safe			
Lock Status Sensor	No		Yes	
Power Input	12VDC at 500mA / 24VDC at 250mA			
Armature Dimensions	185 x 38 x 12.5mm	185 x 38 x 12.5mm	185 x 38 x 12.5mm	185 x 38 x 12.5mm
Magnet Dimensions	250 x 47.2 x 26.5mm	228 x 38 x 27mm	250 x 47.2 x 26.5mm	228 x 38 x 27mm

## Accessories | Electronic Magnetic Locks

Model	ACDSW100	ACDSW101	ACDSW102
Image			
Type	Hard Button	Hard Button	Touch Button + Green/Red LED
Output Contacts	3 (N.O, N.C, COM)	2 (N.O, COM)	3 (N.O, N.C, COM)
Output Rating	3A at 36VDC	3A at 36VDC	2A at 30VAC/DC
MTBF		500,000 uses	
Construction	Sandblasted Aluminium	Aluminium	Aluminium
Dimensions	86 x 50 x 28.9mm	86 x 28 x 20mm	120 x 76 x 18mm