



## NC317XA Security Camera

Easy to install with a 2.8-12mm motorised lens. Control the optical zoom level on installation from the mobile app or NVR.

**5**  
MEGA  
PIXELS

**ZOOM**  
LENS

### Specifications

<b>Camera Type</b>	Bullet
<b>Image Sensor</b>	1/2.7" Progressive CMOS
<b>Maximum Video Resolution (Megapixels)</b>	5
<b>Maximum Video Resolution</b>	2592 x 1944
<b>Lens</b>	2.8-12 mm (H.FOV: 116 to 34°)
<b>Lens Type</b>	Motorised Zoom
<b>Maximum Night IR Distance (M)</b>	40
<b>Image clarity</b>	3.5
<b>Connectors</b>	RJ-45
<b>Video Compression</b>	H.265, H.264
<b>ONVIF (depends on firmware version)</b>	2.6
<b>Operating Environment</b>	-30 to +55°C/less than ≤ 95% RH
<b>Dimensions</b>	Ø84 X 240mm
<b>Weight (Net)</b>	0.94
<b>Accessories</b>	IV2422X, IV2477X
<b>Power Supply</b>	Power over Ethernet IEEE 802.3af, DC12V
<b>Power Consumption</b>	<7W
<b>Connectors (web)</b>	RJ-45 , DC Power Input
<b>Outdoor Use</b>	Yes
<b>IP Rating</b>	IP66
<b>Vandal Resistant</b>	Yes
<b>Frame Rate at Resolution</b>	15
<b>Day/Night Mode</b>	Auto
<b>Image Enhancement</b>	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue
<b>Video Compression</b>	H.265, H.264 (2 streams)
<b>Protocols</b>	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SNMP, P2P (QR code)
<b>Software</b>	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app
<b>Power Over Ethernet</b>	Yes
<b>Ethernet</b>	Ethernet (10/100 Base-T)
<b>UPNP</b>	Yes
<b>In The Box</b>	Free Software available from FAQ, Printed quick user guide, installation template, mounting screws and plugs
<b>Warranty</b>	3 Year Warranty