



Serious jobs made simple.

Compact Series: NVRs available in 4, 8 and 16 channels with PoE

Watchguard[™] Compact Series network video recorders offer Ultra HD broadcast-quality image performance, built-in PoE and rapid remote view setup via QR code, all in a compact size for residential or commercial applications.

- Record Ultra HD up to 8.0MP (3840 x 2160)
- Up to 128Mbps incoming bandwidth; H.265+ support
- 10TB HDD support for up 20TB footage storage
- Remote view in seconds with setup via QR code
- Native Ultra HD live view on 4K monitors via HDMI
- Built-in PoE switches for easy install across the range
- Backup footage via network, USB or SATA devices
- Live view, playback & record via your phone/tablet





Built-in Power over Ethernet



Comprehensive Remote View

Watchguard

Compact Series NVRs | Series Specifications

Model	4 Channel NVR	8 Channel NVR	16 Channel NVR
Product Image			
Ordering Information	NVR4COM3: 4CH, 80Mbps	NVR8COM3: 8CH, 80Mbps	NVR16COM3: 16CH, 128Mbps
Main Processor		Industrial grade embedded processor	
Operating System		Embedded Linux	
Video Input	4 channel	8 channel	16 channel
Two-way Talk	1 channel input, 1 channel output, RCA		
Interoperability	ONVIF (Profile S), CGI, SDK, RTSP		
Video Output	1 x HDMI, 1 x VGA		
Display Resolution		Configurable from 3840 x 2160 to 1024 x 768	
Display Split	1/4	1/4/8/9	1/4/8/9/16
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording		
Recording Resolution	Configurable from 8.0MP (3840 x 2160) to CIF (352 x 288)		
Network Bandwidth	80Mbps for access / 80Mbps for	storage / 60Mbps for forwarding	128Mbps for access / 128Mbps for storage / 64Mb for forwarding
Decoding Capability	4 channels @ 4.0MP (25fps)	8 channels @ 1080p (25fps)	16 channels @ 720p (25fps)
Video Compression	H.265+ / H.265 / H.264+ / H.264		
Record Modes	Manual / Schedule (Regular [Continuous], Motion Detection, Alarm, Timed) / Stop		
Alarm Input / Output	N/A	N/A	4 alarm inputs / 2 alarm outputs
Trigger Events		Z, Tour, Alarm, Video Push, Email, FTP, Snapshot, Buzzer, S	
Video Detection	General: Motion Detection, Smart Motion Detection, Video Loss, Privacy Masking, IPC Alarm Anomaly: Device Offline, Storage Error, Network Security Anomaly, IP/MAC Conflict		
Playback Sync	1/4 1/4/8 1/4/8/16		
Search Modes	Time/Date, Alarm, Motion Detection, Exact Search (to the second), Smart Search		
Backup Modes		USB Device / Network	
Ethernet	1 x RJ-45 port (10/100Mbps)	1 x RJ-45 port (10/100Mbps)	1 x RJ-45 port (10/100/1000Mbps)
Power over Ethernet	4 ports (IEEE802.3at/af , 10/100Mbps)	8 ports (IEEE802.3at/af , 10/100Mbps)	16 ports (IEEE802.3at/af , 10/100Mbps)
Network Functions	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, P2P		
Optical Interface	N/A		
Max. User Access	128 users		
Remote View	iOS (iPhone, iPad) / Android devices		
Internal HDD	1 x SATA III port, up to 10TB 2 x SATA III port, up to 20TB		
HDD Modes		Single (no RAID compatibility)	
USB Interface		2 ports: Rear USB2.0 / Front USB2.0	
Auxiliary Inputs	N/A	N/A	1 x RS232 port
Power Supply Power Consumption	48VDC ~ 53VDC / 1.13A ~ 1.25A < 10W (without HDD) / PoE: Max 25.5W per port,	48VDC ~ 53VDC / 1.8A ~ 2A < 10W (without HDD) / PoE: Max 25.5W per port,	100~240VAC / 47 ~63 Hz / 3.5A < 10W (without HDD) / PoE: Max 25.5W per por
Operating Environment	36W total	72W total -10 ~ 55°C / 10 ~ 90%RH	117W total
Dimensions / Rack Units	260 x 225 x 48mm / 1U	260 x 225 x 48mm / 1U	375 x 320 x 48mm / 1U
Weight	0.86kg (without HDD)	0.92kg (without HDD)	2.63kg (without HDD)
Product Diagrams			

Your local Watchguard[™] professional:

www.activeonline.com.au 1300 816 742