

NEPAWCLS

Neptune Press to Exit,ANSI,IP65,NO/NC/C,LED,1.7mm SS



Description

Neptune classic exit button with LED. Contact rating: 3A/125-250VAC. Power: 12VDC. Output contact: NO/NC/COM. Mechanical life: 100,000 tested. LED colour: Blue. Panel: 1.7 mm thick 304 stainless steel. Operating temp: -20°C~+55°C. Operating humidity: 0-95%(relative humidity). Surface mount: Optional NEASMB metal back box. Installation Diameter: 19 mm. Fixing centres: 83 mm. Dimensions: 115 (L) x 70 (W) x 40 mm (D). Weight: 0.122kg. IP rating: IP65.

Related Products



NEASMB
Neptune ANSI Size Mounting Box

NEASMB

Neptune ANSI Size Mounting Box



Description

Neptune ANSI size surface mounting box to suit Neptune exit buttons. Made from zinc alloy. Supplied with 22 mm cable hole at rear. 4 fixing points. Dimensions 115 (L) x 70 (W) x 28 mm (H).

Related Products



NETACLS

Neptune Touch to Exit, ANSI, NO/NC/C, LED, 1.7mm SS



NETACLB

Neptune Touch to Exit, ANSI, NO/NC/C, LED, 0.9 SS



NENACLB

Neptune Touchless Exit, ANSI, NO/NC/C, LED, 0.9mm SS



NENACLBBD

Neptune Touchless Exit, ANSI, NO/NC/C, LED, 0.9mm SS, 12-24V

ACTIVE ONLINE