



NC591XA Security Camera

SONY image sensor, long-range IR 150 with 22 times zoom lens. This camera is very impressive when patrolling large properties. Options for power AC 24V/DC 12V/POE+





SONY IMAGE SENSOR

Specifications

Camera Type	PTZ
Image Sensor	1/2.8" Progressive CMOS
Maximum Video Resolution (Megapixels)	2
Maximum Video Resolution	1920 x 1080
Lens	4.7mm -104mm (H.FOV: 72 to 3.8°)
Lens Type	Motorised Pan, tilt and Zoom
Maximum Night IR Distance (M)	150
Image clarity	3.5
Connectors	RJ-45 , Analog Video Out, Audio In, Audio Out, Alarm in or out *4
Video Compression	H.265, H.264
ONVIF (depends on firmware version)	19.12
Operating Environment	-20°C to 55°C (14°F-131°F) Humidity: 20%-80% RH
Weight (Net)	2
Power Supply	Power over Ethernet IEEE 802.3at, DC12V, AC24V
Power Consumption	<25W
Connectors (web)	RJ-45 , DC Power Input, Analog Video Output, Audio In, Audio Out, Alarm in or out *4.
Outdoor Use	Yes
IP Rating	IP66
Vandal Resistant	Yes
Frame Rate at Resolution	25
Day/Night Mode	Auto
Image Enhancement	Rotate, Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue
Video Compression	H.265, H.264 (3 streams)
Audio Streaming	Yes – input connector for external mic
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SMTP, P2P (QR code)
Intelligent Video	Pre-set Patrol. Also other cameras can trigger a preset in the PTZ
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app
Power Over Ethernet	Yes
Ethernet	Ethernet (10/100 Base-T)
UPNP	Yes
In The Box	Free Software available from FAQ, Printed quick user guide, Installation template, Mountin screws and plugs
Warranty	3 Year Warranty

https://www.activeonline.com.au/shop/ip-cctv/ivsec/ip-cameras/ivsec-speed-dome-2mp-25fps-4-7-104-mm-lens-poe-ip66-150m-ir-ptz/