



Active Online



# Oversee entire operations.

## NVD-A Series: Ultra HD network video decoders with 6/9 video outputs

The NVD-A Series of IP video decoders allows for configuration of up to 9 HDMI displays, creating video walls that display live footage from any camera or recorder connected to the network, plus any connected HDMI video inputs. Each decoder can be fully configured and adjusted over the network or with SmartPSS.

- Roaming decoder displays all video feeds on network
- Video wall splicing for up to 36 displays per monitor
- Split screen control with zoom/merge/roam/overlay
- Switch between standard & high definition streams
- Decode up to 12CH 4K, 48CH 1080p or 144CH D1
- Support for audio, alarm, bi-directional talk, RS232, RS485, fisheye dewarp & multi-video split display
- Manage via web browser or VIP Vision™ SmartPSS







Decode up to 48 Channels in 1080p



Powerful User Management



Decode up to 144 Display Devices

Model	NVD-A6	NVD-A9
System	 	
	Processor: Internal Processor	
	Operating System: Embedded Linux	
	Video Format: H.265+ / H.265 / H.264 / MJPEG / MPEG4 / MPEG2	
Performance	Audio Format: PCM / G.711 / AAC	
	Video Decoding Capacity (Separate): Port 1~3: 3CH@12MP(15fps), 4CH@8MP, 16CH@1080p, 36CH@720p, 64CH@D1 Port 4~6: 3CH@12MP(15fps), 4CH@8MP, 16CH@1080p, 36CH@720p, 64CH@D1	
	Video Decoding Capacity (Total): 2CH@32MP, 8CH@8MP, 32CH@1080p, 72CH@720p, 128CH@D1	
	Decoding Resolution: 32MP / 12MP / 8MP / 6MP / 5MP / 3MP / 1080p / 720p / 960H / D1 / HD1 / 2CIF / CIF / QCIF	
	Video Frame Rate: PAL: 1~25fps / NTSC: 1~30fps	
	Video Input: 2 x HDMI, 2 x DVI-I	
	Video Output: 6 x HDMI	
	Collection Resolution: Up to 3840 x 2160 (4K / 8MP)	
	Display Resolution: 3840 x 2160 / 2560 x 1600 / 1920 x 1080 / 1280 x 1024 / 1280 x 720 / 1024 x 768 (4 ports support 3840 x 2160, 2 ports support 2560 x 1600)	
	Display Split: 1 / 4 / 6 / 8 / 9 / 16 / 25 / 36 or Free Split	
	Audio Output: 6 x HDMI (embedded)	
	Bi-directional Talk: 1 Pair 3.5mm jack (2.0V line in / 50mV mic in / 10KΩ, 2.0V16Ω out)	
	Alarm Input/Output: 4 channel input / 4 channel relay output (30VDC 1A, 125VAC, 0.5A)	
	Communication Interface: 2 x RJ45 network port (10M/100M/1000M), 3 x RS232(2 x RJ45, 1 x DB9), 1 x RS485	
Environment	Power Supply: 100 ~ 240VAC, 50Hz-60Hz	
	Power Consumption: ≤70W	
	Operating Temperature: -10°C ~ +55°C, 10%~95%RH (86Kpa ~ 106Kpa)	
	Dimensions: 440 x 408 x 70mm (1.5U)	
	Weight: 4.83kg	
Application	 <p style="text-align: center;">NVD-A6</p>	
	 <p style="text-align: center;">NVD-A9</p>	

Your local VIP Vision™ IP solutions professional:

[www.activeonline.com.au](http://www.activeonline.com.au) 1300 816 742