

Perfect intercom upgrades.

2-Wire Hybrid Series: Upgrade existing analogue and 2-wire intercoms

VIP Vision[™] 2-wire residential video intercoms are the perfect upgrade solution to your old intercom or door bell system. Perform incredibly fast upgrades using existing 2-wire infrastructure, without the need for any configuration. Optionally, connect the system to the Internet via the WiFi monitor for remote view and operation.

- 2.0MP wide angle door camera with IR illuminator
- Door stations calls all programmed indoor monitors
- Interfaces with most electric door strikes/mag. locks
- IP65 & IK07 front panel of camera w/ tamper switch
- 7" capacitive touchscreen indoor intercom monitor
- Visitors can leave video messages for unanswered calls (intercom monitor SD card required)
- WiFi monitor for remote monitoring via the app



2-Wire Series | Series Specifications

	Model	INTRDS-H
General	Product Image	
	Main Processor	Embedded Processor
	Backlit Interface	N/A
	Card Support	N/A
	Tamper Detection	Yes
	Camera System	1/2.8" 2.0 MP CMOS HDR Camera Horizontal FoV: 110° ; Vertical FoV: 60°
era	Video Resolution	960 (H) x 576 (V) @25fps
Camera	Audio Input	1
Ű	Audio Output	Built-in Loudspeaker
	Bidirectional Talk	Support
	Network Protocol	TCP/IP
Б	Vandal Resistant	IK07
lent	Ingress Protection	IP65
Environmental	Installation	Flush Mount;Surface Mount via INTCON-H Controller
vir	Power Input	
۵ ش	Power Consumption Weight / Dimensions	≤ 1.5 W (standby), ≤ 10 W (working) 0.502kg / 130 x 96 x 28.5mm
	weight / Dimensions	
		96.0 mm
Accessories	校 [] []	
		[[1] 1] 5 8

VIP Vision[™] 2-Wire Intercom Kit

Model: INTKIT-H


The INTKIT-H offers everything you need to setup a single door camera & indoor monitor over existing 2-wire cabling, and connect to the internet for remote view.

INTKIT-H inclusions:

- 1 x INTRDS-H: 2.0MP Intercom Door Station
- 1 x INTMON-H: 7" Touchscreen Indoor Monitor
- 1 x INTCON-H: 1 x 2-wire Input Module with 1 x Extender Module and 1 x Terminating Modules
- 1 x INTIPRDSGSB: Door Station Surface Mount
- 1 x Alarm I/O leads & DC plug-to-2-wire lead
- 1 x Mounting kits for door station & monitor
- 1 x 48VDC Power Supply

Your local VIP Vision[™] Intercom solutions professional:

	Model	INTMON-H	
	Product Image	HAN5 ·	
	Main Processor	Embedded Processor	
<u> </u>	Video Compression	H.264	
Monitor	Audio Input/Output	1 input ; Built in Loudspeaker	
Ŵ	Audio Bit Rate	16 kHz; 16 bit	
	Bidirectional Talk	Half-Duplex with Door Station; Full-Duplex with App	
	Display Size	7" Colour TFT LCD	
	Display Resolution	1024 (H) x 600 (V)	
	Alarm Support	6 Input channels / 1 output channel / 1 x RS485	
	Operational Input	Capacitive Touchscreen	
	Internal Capacity	Up to 64GB MicroSD Card (sold seperately)	
	Wi-Fi	IEEE802.11b/802.11g/802.11n	
	Network Protocol	IPv4; UDP; DNS; TCP	
ntal	Operating Temperature	-10 °C to +55°C	
me	Installation	Surface wall mounting bracket & kit	
Environmental	Power Output	1 (12 V, 200 mA)	
ED	Power Consumption	\leq 2.5 W (standby), \leq 10 W(working)	
	Weight / Dimensions	0.633kg / 130 × 189 × 23.9 mm	
Accessories			



www.activeonline.com.au 1300 816 742