

# Durafon - SI







Duraton SP935-SIP

### LONG RANGE SIP CORDLESS PHONE SYSTEM:

- > Up to 10 km's line of sight range\*
- > Up to 10 Handsets
- > Up to 10 SIP Accounts

### **OPEN SPACE COVERAGE:**

## Up to 20,000 hectares\*

Mining, primary production, airports, nurseries.

Office Series

SIP-933

### **IN-BUILDING COVERAGE:**

# Up to 12 floors per base\*

Hotels, office blocks, warehouses, hospitals.

### Features:

- > Direct indial for up to 10 handsets
- > Works with all popular IPBX Systems
- > Can be used as a hosted system.
- > Durable, Long-Range SIP Cordless Phone System
- > Up to 12 Floors In-Building Penetration, 250,000 M2 of Facility Coverage, 20,000 hectares of Property, Open Land Coverage\*
- > Base Supports up to Four (4) Concurrent Calls (4-SIP plus cordless to cordless)
- > Works with any IP-PBX that Supports the Standard SIP Protocol
- > Independent 2-Way Intercom
- > "Push-to-Talk" (PTT) Broadcast Feature
- > Proven Durability with Ruggedized Design

- > The Durafon SIP supports up to 10 SIP
- > Direct In-dial the 1-10 cordless handsets.
- > Install the FS SIP Base behind an IPBX System, or hosted cloud PBX.
- > Office Series or Industrial Durafon
  - handset option \* With an external antenna

































### **EnGenius Durafon Features:**

- > Two-way radio, independent of the base unit. Gives handset to handset communication.
- > Rugged splashproof housing\*
- > Broadcast facility direct announcement to all handsets or a group of handsets
- > SMS messaging between handsets\*
- > PABX compatible
- > Programmable PABX option key
- > Call Manager. Program handsets by individual base unit to receive calls or transfer calls only\*
- > Caller ID and Caller ID on Call Waiting tones 30 calls (network dependent)
- > PBX call transfer announced or unannounced
- Intercom call transfer announced or unannounced
- > High capacity Li-ion battery. 6 hours' talk time and 50 hours' standby time
- > Battery change with call on hold
- > Vibration alert mode
- > Four line illuminated LCD display
- > Digital privacy and clarity
- > Key Guard to prevent accidental dialling
- > Call timer

- > 50 name/number speed dial memory
- > Auto power management
- > Call hold
- > Mute/flash/last number redial
- > Signal strength indicator
- > Six level volume control
- > Any key answer option
- > User-defined long distance dialling prefix
- > Four level keytone volume
- > Low battery alarm and display
- > Four selectable keytones
- > Hearing aid compatible
- > Two handset antennas included
- > Audio in socket for music or message on hold
- > Headset socket
- > Car charger socket\*
- > Convenient belt clip
- > Wireless door station compatible
- > Door release relay compatible
- > Optional high gain outdoor antennae
- > One year all-component warranty

### SP935 Durafon SIP Features:

- > Direct indial for up to 10 handsets
- > Works with all popular IPBX Systems
- > Can be used with a hosted system.

# EnGenius® Durafon-SIP 01 new call REDIAL MENU BROADCAST TALK 2-WAY NTERCOM 1 2 ABC 4 GHI 5 JKL 6 MNO 7 PORS 8 TUV 9 WXYYZ WXYZ DURAFON DURAFON

DuraFon SP935-SIP Handset

**Aristel** 

### EnGenius Durafon Model Comparison

Feature	Durafon SN902 1x	Durafon SN 901 1x	Durafon SP9228 4x	Durafon SP935 SIP
Lines/Ports	1 - 4 (1ports/base)	1 - 4 (1ports/base)	1 - 32 (4 ports/base)	1 PSTN + 10 SIP
Multiple Bases	Yes	Yes	Yes	No*
Programmable PBX Functions	Yes	Yes	Yes	Yes
Speakerphone function	Yes	Yes	Yes	Yes
PSTN or analog ports	Yes	Yes	Yes	Yes
Handset to base intercom	Yes	No	Yes	Yes
Auto attendant	No	No	Yes	No
Broadcast all/broadcast group	Yes	Yes	Yes	Yes
Secure, private communications	Yes	Yes	Yes	Yes
Broadcast from cordless extension	Yes	Yes	Yes	Yes
Broadcast from desk phone	No	No	Yes	No
Talk time	6 hrs	6hrs	6hrs	6hrs
Standby time	50 hrs	50 hrs	50 hrs	50 hrs
Durable rubberised case	Yes	Yes	Yes	Yes
Handset capacity base/system	4/36	4/36	8/90	1/10
External antenna option	Yes	Yes	Yes	Yes

Your dealer:			

Aristel Networks Pty Ltd 1/25 Howleys Rd Notting Hill Vic 3168 Freecall: 1800 00 21 33 www.aristel.com.au